2-JAW PARALLEL GRIPPERS **SERIES GP100**

PRODUCT ADVANTAGES



"The precise"

Gripper jaws 20% longer than similar products

Low-backlash ball guide, guided into a steel housing, for maximum precision

Near constant gripping force for different gripper jaw lengths

Makes it possible to cover a high range of variants with only one gripper

► Failure-free continuous operation

Our uncompromising "Made in Germany" quality guarantees up to 10 million maintenance-free gripping cycles

▶ THE BEST PRODUCT FOR YOUR APPLICATION




Our products love the challenge!

Extreme conditions, all over the world—our tried and tested components and systems give you limitless possibilities: Find the best product for your specific use: www.zimmer-group.de

BENEFITS IN DETAIL

- 1 Gripper jaw
 - individual gripper finger mounting
- 2 Wedge hook mechanism
 - synchronized the movement of the gripper jaws
 - high force transfer
- 3 Ball guide
 - smooth running guides via rolling friction
 - near constant force in various gripping jaw lengths
- 4 Removable centering sleeves
 - quick and economical positioning of the gripper fingers

- 5 Mounting block
 - mounting for inductive proximity switch
- 6 Mounting and positioning
 - mounting possible from several sides for versatile positioning
- 7 Drive
 - double-acting pneumatic cylinder
- 8 Energy supply
 - possible from several sides



► FURTHER INFORMATION IS AVAILABLE ONLINE



Technical Information

All information just a click away at: www.zimmer-group.de Find data, illustrations, 3D models and Installation instructions for your installation size using the order number for your desired product. Quick, clear and always current.




2-JAW PARALLEL GRIPPERS **SERIES GP100**

Installation Size: GP103


RD	Dimension			
1	Width	Heigh	t	Depth
H L	[mm]	[mm]		[mm]
W D	34	35		17
My Mx Force and moment				
Mr	Mr	Mx	Му	Fa
41178	[Nm]	[Nm]	[Nm]	[N]
Fa↓	0.5	0.5	0.5	80
► Technical Data*				
	Stroke per jaw	Gripping	force [N]	Weight
Order no.	[mm]	opening	closing	[kg]
GP103	3	41	21	0.09

^{*}All data measured at 6 bar

Gripping force diagram




Installation Size: GP104




^{*}All data measured at 6 bar

Gripping force diagram




Installation Size: GP105



^{*}All data measured at 6 bar

Gripping force diagram




Installation Size: GP110


matanation dize: di 110				
(P)	▶ Dimension			
	Width	Heigh	t	Depth
H	[mm]	[mm]		[mm]
₩ D	80	62		40
My Mx ► Force and moment				
Mr	Mr	Mx	Му	Fa
41178	[Nm]	[Nm]	[Nm]	[N]
Faî	8	8	8	250
► Technical Data*				
	Stroke per jaw	Gripping force [N] Weight		Weight
Order no.	[mm]	opening	closing	[kg]
GP110	10	430	380	0.9

^{*} All data measured at 6 bar

Gripping force diagram




Installation Size: GP115




* All data measured at 6 bar

Gripping force diagram



2-JAW PARALLEL GRIPPERS **SERIES GP100**

ACCESSORIES



► Installation Size: GP103	
Accessories	Order no.
Universal Jaw Aluminium	UB103
Universal Jaw Steel	UB103ST
Inductive proximity switch - Cable 5 m	NJ4-E2
Plug-in connector Straight Cable 5m - Socket M8 (female)	KAG500
Plug-in connector Angled Cable 5m - Socket M8 (female)	KAW500
Straight Fittings - Barb Style Connection	GVM3
Angled Fittings - Barb Style Connection	WVM3
Delivery contents	Order no.
Centering Disc	BDST10300
Mounting block	KB4-02
	Accessories Universal Jaw Aluminium Universal Jaw Steel Inductive proximity switch - Cable 5 m Plug-in connector Straight Cable 5m - Socket M8 (female) Plug-in connector Angled Cable 5m - Socket M8 (female) Straight Fittings - Barb Style Connection Angled Fittings - Barb Style Connection Delivery contents Centering Disc

	► Installation Size: GP104	
Pos.	Accessories	Order no.
1	Universal Jaw Aluminium	UB104
1	Universal Jaw Steel	UB104ST
4	Inductive proximity switch - Cable 5 m	NJ4-E2
5	Plug-in connector Straight Cable 5m - Socket M8 (female)	KAG500
5	Plug-in connector Angled Cable 5m - Socket M8 (female)	KAW500
6	Straight Fittings - Quick Connect Style	GVM5
	Delivery contents	Order no.
2	Centering Disc	BDST40400
3	Mounting block	KB4-03

	► Installation Size: GP105	
Pos.	Accessories	Order no.
1	Universal Jaw Aluminium	UB105
1	Universal Jaw Steel	UB105ST
4	Inductive proximity switch - Connector M8	NJ6.5-E2S
4	Inductive proximity switch - Cable 5 m	NJ6.5-E2-01
5	Plug-in connector Straight Cable 5m - Socket M8 (female)	KAG500
5	Plug-in connector Angled Cable 5m - Socket M8 (female)	KAW500
6	Straight Fittings - Quick Connect Style	GVM5
	Delivery contents	Order no.
2	Centering Disc	BDST40400
3	Mounting block	KB6.5-03

	► Installation Size: GP110	
Pos.	Accessories	Order no.
1	Universal Jaw Aluminium	UB110P
1	Universal Jaw Steel	UB110PST
4	Inductive proximity switch - Cable 5 m	NJ8-E2
4	Inductive proximity switch - Connector M8	NJ8-E2S
5	Plug-in connector Straight Cable 5m - Socket M8 (female)	KAG500
5	Plug-in connector Angled Cable 5m - Socket M8 (female)	KAW500
6	Straight Fittings - Quick Connect Style	GVM5
	Delivery contents	Order no.
2	Centering Disc	BDST40800
3	Mounting block	KB8-25

	► Installation Size: GP115	
Pos.	Accessories	Order no.
1	Universal Jaw Aluminium	UB115
1	Universal Jaw Steel	UB115ST
4	Inductive proximity switch - Cable 5 m	NJ8-E2
4	Inductive proximity switch - Connector M8	NJ8-E2S
5	Plug-in connector Straight Cable 5m - Socket M8 (female)	KAG500
5	Plug-in connector Angled Cable 5m - Socket M8 (female)	KAW500
6	Straight Fittings - Quick Connect Style	GV1-8X8
	Delivery contents	Order no.
2	Centering Disc	BDST11500
3	Mounting block	KB8-26